



F.No.32-54/AE-IV/JE(6)/OM/2024-25  
**OULGARET MUNICIPALITY**  
**PUDUCHERRY - 5**

Jawahar Nagar, the 20.03.2025

**SHORT QUOTATION NOTICE**

On behalf of the Municipal Council sealed quotations are invited from the eligible firms/contractors by the undersigned for the following work:

Name of Work: Urgent repairing and replacement of defective spares of Non burning of High-mast lighting system at Karuvadikuppam Municipal Burial Ground.

| Sl. No. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Quantity     | Rate per unit | Total amount |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------------|--------------|
| 1.      | Supply of 2.5 sq. mm x 8 core PVC sheathed multicore flexible copper cable Make : Finolex/ Polycab/ Power-flex/ Havells.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 22.00 Metres |               |              |
| 2.      | Supplying and making end termination with brass compression gland and aluminium lugs for following size of PVC insulated and PVC sheathed / XLPE aluminium conductor cable of 1.1 kV grade as required - 4 X 25 sq.mm (19mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 4.00 Nos.    |               |              |
| 3.      | Fixing testing and commissioning of Sodium vapour / Mercury vapour / Metal halide street light fittings on existing poles as required                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 6.00 Nos.    |               |              |
| 4.      | <p>Fabrication, supply, erection, testing and commissioning of one no of SMC Box (Make: Sintex) with metering and timer panel panel board for the power supply of over all size 850mm x 350mm x 250mm made out of glass wool with resin material. The front top portion have energy meter with viewing glass with 10mm hylem sheet. The bottom side compartments with 40 - 63A rating, TPN MCB, "C Series, 10KA breaking capacity (Make - Siemens/ABB), 1no. of Timer switch (Daily) analog with battery backup to 200hrs. (Make - L&amp;T - Hagger/ Legrand - Lexic), 1no. 60A power contactor (Make - C&amp;S), 1no. of toggle switch (Make - C&amp;S), 3nos of signal lamp (Blue, Red, Yellow).</p> <p>The switch units are to be fixed with in the allotted size in the 10mm hylem sheet. The bottom sheet of the shell should be of PVC thick cold rolled for cable entry. The panel has to be mounted with required concreting and supports. Interior connection between the switch fuse units are to be done with 2.5sqmm / 6.0 / 10.0sqmm ISI marked, FR PVC insulated, single core copper conductor cable. (Make - Finolex / Polycab).</p> <p>The door should be of flush type inter locking in one position. The panel provided with removable type gland plated to the bottom and with sufficient holes of required diameter and Earth work excavation, filling river sand and P.C.C.of 1:2:4 ratio for the required size. The cost should be inclusive of minor modification suitable for site condition as approved by the engineer - in - charge.</p> | 1.00 No.     |               |              |


|    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |              |  |  |
|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--|--|
| 5. | Lowering and lifting the High mast lantern                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 1.00<br>No.  |  |  |
| 6. | Supply and fixing of LED flood light luminaries 200W (Power output ), suitable for high mast bracket, white light with pressing die cast aluminium, Diffuser clear toughen glass housing IP 65/66, efficacy> 110Lm/Watt, LED chip package 5050, CRI> 70, rated voltage : 240V, rated frequency 50HZ safe operating voltage range 140V-280V AC and with necessary over voltage, short circuit open circuit & surge protection. The luminaries shall be warranted for three years on site replacement /rectification. The NABL type test report, Driver safety test report as per BIS, LM80 report from chip manufacturer shall be furnished. (Make:- Philips/Havells/Crompton/Everyday/Bajaj). | 6.00<br>Nos. |  |  |
| 7. | Supply & Laying of Potential Earth Electrodes Model STANDARD PS53C 48mm dia, wall thickness 3.25mm, terminal size :32 x 10 mm, terminal hole dia 12 mm, hot dip galvanized 80 to 100 microns, 3 meler long, pipete inner space filled with high conductive material, including 2 bags (25kg per bag) of Earth Life Compound , as IS 3043. Base Metal :IS marked branded miled steel pipes.                                                                                                                                                                                                                                                                                                    | 2.00<br>Nos. |  |  |
| 8. | Providing and fixing 4.00 mm dia copper wire on surface or in recess for loop earthing along with existing surface / recessed conduit / submain wiring / cable as required.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 24.00<br>Mts |  |  |
| 9. | Providing and fixing of straight through cable jointing kit with cast resin compound with ferrules for 4x35Sqmm 1.1KV grade cable..                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 2.00<br>Set  |  |  |

Quotation will be received by the undersigned up to 3.30 pm on 28-03-2025 and opened at 4.00 p.m. on the same day.

EMD at 2.00% of the quoted amount should be remitted in the form of demand draft in favour of the Commissioner, Oulgaret Municipality. Quotation should be valid for 90 days from the date of opening.

The Oulgaret Municipal Council reserves right to reject any or all the quotations without assigning any reason thereof. The Oulgaret Municipality Council is competent to accept any quotations.

The rate quoted should be inclusive of all charges viz. tax, transporting etc.

  
(A.SURESHRAJ)  
COMMISSIONER

**Copy to:**

1. Notice Board, Oulgaret Municipality.
2. Oulgaret Municipality Website.

Quotation notice