



F.No.32-60/AE-IV/JE(6)/OM/2025-26

OULGARET MUNICIPALITY

PUDUCHERRY – 5

Jawahar Nagar, the 13.07.2026

SHORT QUOTATION NOTICE (2nd Call)

On behalf of the Municipal Council sealed quotations are invited from the eligible firms/contractors by the undersigned for the following work:

Name of Work: Construction of Toilet Block at 4th Cross Street of Rainbow Nagar Park in Rainbow Nagar, Kamaraj Nagar Constituency.

Sl. N o.	Descriptions	Quantity	Rate per unit	Total amount
1.	Earthwork in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, for all lift, including getting out the excavated soil and disposal of surplus excavated soil as per direction of Engineer-in-charge , within a lead of 50m - all kinds of soil	4.50 Cum	1Cum (One Cubic meter)	
2.	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - all work upto plinth level - 1:5:10 (1 cement : 5 fine aggregate : 10 graded stone aggregate 40mm nominal size)	1.50 Cum	1Cum (One Cubic meter)	
3.	Providing and laying in position specified grade of reinforced cement concrete , excluding the cost of centering , shuttering , finishing and reinforcement - All work upto plinth level 1:1.5:3 (1cement : 1.5 fine aggregate : 3 graded stone aggregate 20 mm nominal size)	1.75 Cum	1Cum (One Cubic meter)	
4.	Reinforced cement concrete work in walls (any thickness) , including attached pilasters, buttresses , plinth and sting courses , fillets , columns , pillars , piers , abutments , posts and struts etc. upto floor five level excluding cost of centering , shuttering , finishing and reinforcement - 1:1.5:3 (1 cement : 1.5 fine aggregate : 3 graded stone aggregate 20mm nominal size)	0.75 Cum	1Cum (One Cubic meter)	
5.	Reinforced cement concrete work in beams, suspended floors , roofs having slope up to 15degree landings , balconies , shelves , chajjas , lintels , bands , plain window sills , staircases and spiral stair cases above plinth level up to floor five level excluding the cost of centering ,shuttering, finishing and	2.00 Cum	1Cum (One Cubic metre)	

	reinforcement , with 1:1.5:3 (1 cement : 1.5 fine aggregate : 3 graded stone aggregate 20mm nominal size)			
6.	Centering and shuttering including strutting , propping etc and removal of form for - foundations, footings, bases of columns etc for mass concrete.	5.00 Sqm	1Sqm (One Square metre)	
7.	Centering and shuttering including strutting , propping etc and removal of form for - Suspended floors , roofs , landings , balconies and access platform	7.00 Sqm	1Sqm (One Square metre)	
8.	Centering and shuttering including strutting , propping etc and removal of form for - Lintels , beams , plinth beams , girders , bressumers and cantilevers.	19.00 Sqm	1Sqm (One Square metre)	
9.	Centering and shuttering including strutting , propping etc and removal of form for - Columns , Pillars , Piers , Abutments , Posts and Struts.	11.50 Sqm	1Sqm (One Square metre)	
10	Steel reinforcement for R.C.C. work including straightening , cutting , bending , placing in position and binding all complete above plinth level - Thermo - Mechanically Treated bars Fe - 500 D or more	681.00 Kgs.	1Kg. (One Kilo Gram)	
11	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 3.5 in foundation and plinth in - cement mortar 1:6 (1 cement : 6 fine aggregate)	1.25 Cum	1Cum (One Cubic metre)	
12	Brick work with common burnt clay F.P.S (non modular) bricks of class designation 3.5 in superstructure above plinth level upto floor five level in all shapes and sizes in - cement mortar 1:6 (1 cement : 6 fine aggregate)	6.00 Cum	1Cum (One Cubic metre)	
13	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 3.5 in superstructure above plinth level upto floor V level - cement mortar 1:4 (1 cement : 4 fine aggregate)	6.00 Sqm	1Sqm (One Square metre)	
14	Extra for providing and placing in position 2 nos 6mm dia M.S.bars at every third course of half brick masonry	6.00 Sqm	1Sqm (One Square metre)	
15	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS:15622(thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green,black of any size as approved, in skirting, risers of steps and dados, over 12mm thick bed of cement mortar 1:3 (1 cement : 3 fine aggregate) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete	31.50 Sqm	1Sqm (One Square metre)	

16	Providing and fixing Fiber Glass Reinforced plastic (FRP) Door Frames of cross section 90 mm x 45 mm having single rebate of 32 mm x 15 mm to receive shutter of 30 mm thickness . The laminate shall be moulded with fire resistant grade unsaturated polyester resin and chopped mat. Door frame laminate shall be 2 mm thick and shall be filled with suitable wooden block in all the three legs. The frame shall be covered with fiber glass from all sides. M.S.stay shall be provided at the bottom to steady the frame	12.00 Meters	1Meter (One Meter)	
17	Providing and fixing to existing door frames - 30mm thick Glass Fibre Reinforced Plastic (FRP) panelled door shutter of required colour and approved brand and manufacture , made with fire - retardant grade unsaturated polyester resin , moulded to 3 mm thick FRP laminate for forming hollow rails and styles , with wooden frame and suitable blocks of seasoned wood inside at required places for fixing of fittings , cast monolithically with 5 mm thick FRP laminate for panels conforming to IS : 14856 , including fixing to frames	5.00 Sqm	1Sqm (One Square metre)	
18	Providing and fixing factory made uPVC white colour sliding glazed window upto 1.50m in height dimension comprising of uPVC multi - chambered frame with in-built roller track and sash extruded profiles duly reinforced with 1.60 + or - 0.2 mm thick galvanized mild steel section made from roll forming process of required length (shape & size according to uPVC profile), appropriate dimension of uPVC extruded glazing beads and uPVC extruded interlocks, EPDM gasket, wool pile , zinc alloy (white powder coated) touch locksN with hook , zinc alloy body with single nylon rollers (weight bearing capacity to be 40 kg), G.I. fastners 100 x8 mm size for fixing frame to finished wall and necessary stainless steel screws etc. Profile of frame & sash shyll be mitred cut and fusion welded at all corners, including drilling of holes for fixing hardware's and drainage of water etc.After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealent over backer rod of required size and of approved quality , all Complete 1.75 sqm) - as per approved drawing.(Single / doubleglass panes , wire mesh and silicon sealent shall be paid separately) - Two track two panels sliding window made of (small series) frame 52 x 44 mm & sash 32 x 60 mm both having wall thickness of 1.9 + or - 0.2 mm and single glazing bead of appropriate dimension.(Area of	1.00 Sqm	1Sqm (One Square metre)	

	window upto sliding window size 1.20x1.35 m			
19	Steel work welded in built up sections / framed work including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required - in gratings, frames, guard bar, ladder, railings, brackets, gates and similar works	29.00 Kgs.	1Kg. (One Kilo Gram)	
20	Providing and laying rectified glazed ceramic flooring tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS :15622 , of approved make , incolours white, ivory, grey, fume red brown, laid on 20mm thick cement mortar 1:4 (1 cement : 4 fine aggregate) ,jointing with grey cement slurry @ 3.3 kg per sqm including grouting the joints with white cement and matching pigments etc., complete	6.00 Sqm	1Sqm. (One Square Meter)	
21	Providing and laying pressed clay tiles (as per approved pattern 18mm nominal thickness of approved size) on roofs jointed with cement mortar 1:4 (1 cement : 4 fine aggregate) mixed with 2% integral water proofing compound , laid over a bed of 20mm thick cement mortar 1:4 (1 cement : 4 fine aggregate) and finished neat complete	7.25 Sqm	1Sqm. (One Square Meter)	
22	Lime concrete terracing on roofs of required thickness laid to fall with 25mm nominal size brick aggregate and 50% lime mortar 1:2 (1 lime putty : 2 surkhi) rammed and finished with gur and belgiri treatment complete including rounding of junctions with Parapet wall complete	0.75 Cum	1Cum. (One Cum Meter)	
23	Providing and fixing on wall face unplasticised rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10mm gap for thermal expansion, (i) Single socketed pipes - 110 mm diameter	8.00 Meters	1Cum. (One Meter)	
24	Providing and fixing on wall face unplasticised-PVC moulded fittings / accessories for unplasticised rigid PVC rain water pipes conforming to IS : 13592 type A including jointing with seal ring conforming to IS : 5382 leaving 10mm gap for thermal expansion. Single Tee with door 110X110X110mm.	2.00 Nos.	1Each. (One Each)	
25	Providing and fixing on wall face unplasticised - PVC moulded fittings / accessories for unplasticised rigid PVC rain water pipes conforming to IS:13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10mm gap for thermal expansion - bend 87.5 degree - 110 mm bend	2.00 Nos.	1Each. (One Each)	

26	Providing and fixing on wall face unplasticised - PVC moulded fittings / accessories for unplasticised rigid PVC rain water pipes conforming to IS:13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10mm gap for thermal expansion - shoe (plain) - 110mm shoe	2.00 Nos.	1Each. (One Each)	
27	Providing and fixing unplasticised - PVC pipe clips of approved design to unplasticised- PVC rain water pipes by means of 50x50x50mm hard wood plugs , screwed with M.S. screws of required length, including cutting brickwork and fixing in cement mortar 1:4 (1 cement : 4 fine aggregate) and making good the wall etc., complete - 110mm	3.00 Nos.	1Each. (One Each)	
28	12 mm cement plaster of mix 1:5 (1 cement : 5 fine aggregate)	38.00 Sqm	1Sqm. (One Square Meter)	
29	15 mm cement plaster on the rough side of single or half brick wall of mix 1:5 (1 cement : 5 fine aggregate)	14.00 Sqm	1Sqm. (One Square Meter)	
30	6mm cement plaster of mix 1:3 (1 cement : 3 fine aggregate)	6.00 Sqm	1Sqm. (One Square Meter)	
31	12mm thick plain cement mortar bands in cm per cement mortar 1:4 (1cement : 4 fine aggregate) - raised band	84.00 Cm / meter	1 Cm / meter.	
32	White washing with lime to give an even shade - new work (three or more coats)	6.00 Sqm	1Sqm. (One Square Meter)	
33	Finishing walls with acrylic smooth exterior paint of required shade - New work (two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre / 10sqm	52.00 Sqm	1Sqm. (One Square Meter)	
34	Painting with synthetic enamel paint of approved brand and manufacutre to give an even shade - Two or more coats on new work	1.00 Sqm	1Sqm. (One Square Meter)	
35	Providing and fixing wash basin with C.I. brackets, 15mm C.P. brass pillar taps ,32 mm C.P.brass waste of standard pattern , including painting of fittings and brackets ,cutting and making good the walls wherever required - white vitreous china flat back wash basin size 550x400 mm with single 15mm C.P. brass pillar tap wherever required - white vitreous china flat back wash basin size 450x300 mm with single 15mm C.P. brass pillar tap	1.00 No.	1Each. (One Each)	

36	Providing and fixing white vitreous china water closet squatting pan (Indian type) - Orissa pattern W.C.pan of size 580x440mm	2.00 Nos.	1Each. (One Each)	
37	Extra for using coloured W.C.pan instead of white W.C.pan - Orissa pattern W.C.pan 580x440mm	2.00 Nos.	1Each. (One Each)	
38	Providing and fixing P.V.C. waste pipe for sink or wash basin including PVC waste fittings complete - semi rigid pipe - 40mm dia	1.00 No.	1Each. (One Each)	
39	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6mm thick hard board ground fixed to wooden cleats with C.P.brass screws and washers complete	1.00 No.	1Each. (One Each)	
40	Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors - 100mm inlet and 75mm outlet - sand cast iron S&S as per IS: 3989	1.00 No.	1Each. (One Each)	
41	Providing and fixing PTMT bottle trap for wash basin and sink - Bottle trap 38 mm single piece moulded with height of 270 mm, effective length of tail pipe 260 mm from the centre of the waste coupling, 77 mm breadth with 25mm minimum water seal, weighing not less than 263 gms	1.00 No.	1Each. (One Each)	
42	Providing and fixing ASTM pipes including all ASTM plain & brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fitting with one step ASTM solvent cement and the cost of cutting chases and making good the same including testing of joints complete (Concealed work including cutting chases and making good the walls etc.) - 20 mm nominal outer dia pipes	10.00 Meters	1Meter. (One Meter)	
43	Providing and fixing ASTM pipes including all ASTM plain & brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fitting with one step ASTM solvent cement and the cost of cutting chases and making good the same including testing of joints complete (Concealed work including cutting chases and making good the walls etc.) - 25 mm nominal outer dia pipes	10.00 Meters	1Meter. (One Meter)	
44	Providing and fixing G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc., - internal work - exposed on wall - 15mm dia nominal bore	3.00 Meters	1Meter. (One Meter)	
45	Providing and fixing brass stop cock of approved quality - 20mm nominal bore	3.00 Nos.	1Each. (One Each)	
46	Providing and fixing unplasticised PVC	1.00	1Each.	

	connection pipe with brass unions - 45 cm length - 15mm nominal bore	No.	(One Each)	
47	Constructing masonry chamber 30x30x50 cm inside , in brick work in cement mortar 1.4 (1 cement : 4 fine aggregate) for stop cock, with C.I. surface box 100x100x75 mm (inside) with hinged cover fixed in reinforced cement concrete slab 1:1.5:3 mix (1 cement : 1.5 fine aggregate : 3 graded stone aggregate 20mm nominal size) , including necessary excavation , foundation concrete 1:5:10 (1 cement : 5 fine aggregate : 10 graded stone aggregate 40mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 fine aggregate) 12mm thick , finished with a floating coat of neat cement complete as per standard design - with common burnt clay F.P.S (non modular) bricks of class designation 3.5	2.00 Nos.	1Each. (One Each)	
48	Providing and fixing C.P.brass bib cock of approved quality conforming to IS: 8931 - 15 mm nominal bore	4.00 Nos.	1Each. (One Each)	
49	Providing and fixing on wall /column face unplasticised - PVC soil and waste pipes (type-B) conforming to IS:13592-199 including jointing with seal ring conformation to IS: 5382 leaving 10mm gap for thermal expansion - single socketed pipes 110mm diameter	5.00 Meters	1Meter (One Meter)	
50	Providing and fixing on wall face/column face unplasticised - PVC moulded fittings / accessories for unplasticised - PVC soil and waste pipes conforming to IS:14735 - 1999 including jointing with seal ring conforming to IS:5382 leaving 10mm gap for thermal expansion - Single tee with door - 110x110x110mm	3.00 Nos.	1Each. (One Each)	
51	Providing and fixing on wall face / column face unplasticised - PVC mould fittings / accessories for unplasticised - PVC soil and waste pipes conforming to IS : 14735 - 1999 including jointing with seal ring conforming to IS : 5382 leaving 10mm gap for thermal expansion - bend 110 mm.	2.00 Nos.	1Each. (One Each)	
52	Providing and fixing on wall / column face unplasticised - PVC soil and waste pipes (type B) conforming to IS :13592 - 1992 including jointing with seal ring conforming to IS : 5382 leaving 10mm gap for thermal expansion - Single socketed pipes 75mm diameter	3.00 Meter	1Meter. (One Meter)	
53	Providing and fixing on wall / column face unplasticised - PVC moulded fittings / accessories for unplasticised - PVC soil and waste pipes conforming to IS :14735 -1999 including jointing with seal ring conforming to IS : 5382 leaving 10mm gap for thermal expansion - Bend 75 mm	1.00 Each	1Each. (One Each)	

2026-2027/Quotation notice

54	Supply of Quarry rubbish including stacking to department gauge for premeasurement and spreading required thickness	3.50 Cum	1 Cum (One Cubic Metre)	
55	Supplying and drawing following sizes of FRLS PVC insulated copper conductor single core cable in the existing surface / recessed steel / PVC conduit as required - 2 X 1.5	90.00 Meters	1 Meter (One Meter)	
56	Supplying and drawing following sizes of FRLS PVC insulated copper conductor single core cable in the existing surface / recessed steel / PVC conduit as required -2 x 2.5 sq.mm	90.00 Meters	1 Meter (One Meter)	
57	Supplying and drawing following sizes of FRLS PVC Insulated copper conductor single core cable in the existing surface / recessed steel / PVC conduit as required -2 x 4 sq.mm	10.00 Meters	1 Meter (One Meter)	
58	Supplying and drawing following sizes of FRLS PVC insulated copper conductor single core cable in the existing surface / recessed steel / PVC conduit as required -2 x 6 sq.mm.	10.00 Meters	1 Meter (One Meter)	
59	Supplying and fixing of following sizes of medium class PVC conduit along with accessories in surface / recess including cutting the wall and making good the same in case of recessed conduit as required - 20mm	10.00 Meters	1 Meter (One Meter)	
60	Supplying and fixing of following sizes of medium class PVC conduit along with accessories in surface / recess including cutting the wall and making good the same in case of recessed conduit as required - 25mm	15.00 Meters	1 Meter (One Meter)	
61	Supplying and fixing metal box of following sizes (nominal per size) on surface or in recess with suitable size of phenolic laminated sheet cover in front including painting etc.as required - 200 mm x 300 mm x 60 mm	4.00 Nos.	1 No (One Number)	
62	Supplying and fixing metal box of following sizes (nominal size) on surface or increcess with suitable size of phenolic laminated sheet cover in front including painting etc.as required - 250 mm x 300 mm x 100 mm	1.00 No.	1 No (One Number)	
63	Supplying and fixing following piano type switch / socket on the existing switch box / cover including connections etc.as required - 5/6 A switch	15.00 Nos.	1 No (One Number)	
64	Supplying and fixing following piano type switch / socket on the existing switch box / cover including connections etc.as required - 2 way 15/16 A switch	2.00 Nos.	1 No (One Number)	
65	Supplying and fixing following piano type switch / socket on the existing switch box / cover including connections etc.as required - 3 pin 5/6 A socket outlet, piano type ISI marked.	4.00 Nos.	1 No (One Number)	

66	Supplying and fixing following piano type switch / socket on the existing switch box / cover including connections etc.as required - 6 pin 15/16 A socket outlet	2.00 Nos.	1 No (One Number)	
67	Supplying and fixing 3 pin , 5 A ceiling rose on the existing junction box / wooden block including connection etc as required	8.00 Nos.	1 No (One Number)	
68	Supplying and fixing PVC batten / angle holder including connection etc.as required.	2.00 Nos.	1 No (One Number)	
69	Providing and fixing following capacity TP&N disconnector fuse switch unit inside the existing panel board with ISI marked HRC fuses including drilling holes in cubicle panel , making connections ,etc , as required - 32 A TP&N	2.00 Nos.	1 No (One Number)	
70	Supplying and fixing following rating , double pole , 240 V, Isolator in the existing MCB DB complete with connections ,testing and commissioning etc.as required - 40 A	2.00 Nos.	1 No (One Number)	
71	Supplying and fixing following rating, double pole , (single phase and neutral), 240V , residual current circuit breaker (RCCB), having a sensitivity current 30 mA in the existing MCB DB complete with connections , testing and commissioning etc as required - 40 A	4.00 Nos.	1 No (One Number)	
72	Earthing with G.I. earth pipe 4.5 meter long, 40 mm dia including accessories , and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. (but without charcoal / coke and salt) as required	1.00 Set	1 Set (One Set)	
73	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 11kV grade of following size direct in ground including excavation, sand cushioning, protective covering and refilling the trench etc.as required - upto 120 sq.mm	31.00 Meters	1 Meter (One Meter)	
74	Supplying and erection of 15 A aerial fuse complete as required	1.00 No.	1 No (One Number)	
75	Supplying and fixing of 32 mm dia x 2.00 metres long per G.I.pipe (medium class) bracket for mounting of fluorescent / HPMV / HPSV street light fitting on pole including bending the pipe to the required shape, 2 nos 40 mm x 3 mm flat iron clamps with nuts , bolts and washer , painting the flat iron with primer and finish paint etc.as required	1.00 No.	1 No (One Number)	

2026-2027/Quotation notice

76	Supplying and Fixing 20mm PVC junction Box, Two Way	20.00 Nos.	1 No (One Number)	
77	Providing and Fixing 20mm PVC Bends – medium class – As per IS : 9537 (Part 3)	10.00 Nos.	1 No (One Number)	
78	Providing and Fixing 25mm PVC Bends – medium class – As per IS : 9537 (Part 3)	10.00 Nos.	1 No (One Number)	
79	Providing and Fixing 1200mm Sweep double ball bearing ceiling fan - make almonard / usha	2.00 Nos.	1 No (One Number)	
80	Providing and Fixing 20 W LED Tube Light Fittings. Make: Philips / Bajaji (or) Equivalent.	4.00 Nos.	1 No (One Number)	
81	Supplying of 4 core X 25 sqmm armoured aluminum U.G cable with I.S.I marks (Make - finolex/Polycab)	37.00 Meters	1 Meter (One Meter)	
82	Providing and Fixing 9W LED Bulb. Make: Philips / Bajaj (or) Equivalent.	4.00 Nos.	1 No (One Number)	

Quotation will be received by the undersigned up to 3.30 pm on 20.07.26 and opened at 4.00 p.m. on the same day.

EMD at 2.00% of the quoted amount should be remitted in the form of demand draft in favour of the Commissioner, Oulgaret Municipality. Quotation should be valid for 90 days from the date of opening.

The Oulgaret Municipal Council reserves right to reject any or all the quotations without assigning any reason thereof. The Oulgaret Municipality Council is competent to accept any quotations.

The rate quoted should be inclusive of all charges viz. tax, transporting etc.

Digitally signed by
Arun Ayavou
Date: 10-07-2026
00:20:28
(R.ARUN AYAVOU)
COMMISSIONER

Copy to:

1. Notice Board, Oulgaret Municipality.
2. Oulgaret Municipality Website.